

# Kohler PW 9000DPA

(10–250 kVA)

Parallelable up to 1.5 MVA

## Technical Specification



# Kohler PW 9000DPA

## General data

System power range	30–1500 kVA
Max power per module	30 kVA / 40 kVA / 50 kVA
Max power per frame	250 kVA
Number of UPS modules in each frame	1 to 5
Weight (with modules / without batteries)	421–439 kg
Dimensions (mm) W x D x H	730 x 800 x 1975
Topology	Online double conversion
Parallel configuration	Up to 30 modules
UPS type	Modular (Decentralised Parallel Architecture)

## Input

Nominal input voltage	3 × 380/220 V + N, 3 × 400/230 V + N, 3 × 415/240 V + N
Voltage tolerance (referred to 3 × 400 / 230 V)	For loads <100% (-25%, +15%), <80% (-30%, +15%), <60% (-40%, +15%)
Input distortion THDi	<3% @ 100% load
Frequency	30–70 Hz
Power factor @ 100% load	0.99

## Output

Output power factor	0.8
Rated output voltage	3 × 380 / 220 V + N, 3 × 400 / 230 V + N, 3 × 415 / 240 V + N
Voltage distortion (referred to 3 × 400 / 230 V)	<±2% with linear load
Frequency	50 Hz or 60 Hz
Overload capability	1 min.: up to 150% / 10 min.: up to 125%
Unbalanced load	100% (all three phases regulated independently)
Crest factor	3 : 1 (load supported)

## Efficiency

Overall efficiency	Up to 95.5%
In eco-mode configuration	99%

## Environment

Storage temperature	-25 °C to +70 °C
Operating temperature	0 °C to +40 °C
Altitude	1000 m without derating

## Battery

Battery capacity	Configurable up to several hours
Internal batteries	240 x 7/9Ah (150 frame) / External batteries only (250 frame)

## Communications

LCD	Yes (per module)
LEDs	LED for notification and alarm
Communication ports U	SB, RS-232, SNMP slot, potential-free contacts

## Standards

Safety	IEC / EN 62040-1
Electromagnetic compatibility (EMC)	IEC / EN 62040-2
Performance	IEC / EN 62040-3
Manufacturing	ISO 9001, ISO 14001, OHSAS18001
Product certification	CE
IP rating	IP 20



**KOHLER** POWER  
uninterruptible

---

Regional Office:

**Kohler Uninterruptible Power**

---

7 Jurong Pier Road  
Singapore 619159

---

**Tel:** +65 6302 0702

---

**Fax:** +65 6302 0717

---

**Email:** [salesUPS.sg@kohler.com](mailto:salesUPS.sg@kohler.com)

---

**[www.kohler-ups.sg](http://www.kohler-ups.sg)**

---